ELECTRIC ARTICULATING BOOM LIFT

AB22EJ PLUS(AB710EJ PLUS)

CompliantwithCE/AS standards

PRODUCT HIGHLIGHTS

Outstanding strength both indoors and outdoors

- Smooth o -road and quiet indoor operation.
- 4WD, 40% gradeability.
- Standard active oscillation, excellent exibility...

Excellent performance, safety and reliability

- Smart display for easy machine status and fault diagnosis.
- Auxiliary power system.
- Rexroth controller comply with ISO13849 standard..

Comfortable and e cient

- The main boom and secondly boom are equipped with angle sensors, to automatically reduce speed and act as a buffer.
- Proportional steering speed reduction technology..



Standard features			
Platform hydraulic leveling	Overload sensing system	360° Continuous Turntable rotation	
Platform 180° hydraulic rotation	Emergency brake release	Drive enable system	
Display screen	Foam- lled non-marking tyres	3 proportional joysticks	
Fault diagnosis system	Lead-acid battery	Horn and buzzer alarms	
Emergency stop system	Rexroth system	Rotating warning lamp	
Emergency lowering system with auxiliary power	Tilt angle up to 5°	2.44m(8') platform	
	Optional features		
1.83 m (6') work platform	AC cable to platform	Overhead anti-collision device	
1.45 m (4'9") work platform	Platform worklight	Inverter 220V AC power supply	
Solid non-marking tires			



Model	AB22EJ PLUS (AB710EJ PLUS